

EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/1599/162/05/18/0996

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment:

Manufacturer:

Description

PPE Type: protective glove against mechanical risks, thermal risks

Product reference: 01-101

Article code : /

Glove description: 15 GAUGES Graphene LINER, Micro foam Nitrile palm coating

Available sizes: 6 7 8 9 10 11

Pictures:







Reference standard:

Levels of performance / class of protection

EN 420:2003+A1:2009

EN 388:2016

4121A

The levels of performance have been measured on the palm

« X »indicates that the glove has not been submitted to the test

EN 407:2004 X 1 X X X X

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from MAY, 2018

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

Issued in Lyon by
Lionel Gaudillere
PPE certification manager



Date of first issue: 28 May 2018 End of validity date: 28 May 2023

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France Tél.: +33 (0)4 72 76 10 10 - Fax: +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product : 01-101

Article code : /

Technical file index : 01

Last update : MAY, 2018

IDENTIFICATION

Reference of the product : : 01-101

Article code : . . /

Basic Model

Technical file index: : 01

Last update : : MAY, 2018

Manufacturer:

Factory:

GLOVE DESCRIPTION

General glove description:

15 GAUGES Graphene LINER, Micro foam Nitrile palm coating type of coating finish: foam

Visual description (picture back and palm sides):



Field of use

Protective gloves against mechanical risk, used in glass industry; Protective gloves against mechanical risk for automotive industry; Aerospace, Appliance manufacturing, Automotive manufacturing, construction, glass work, logistics, packaging, metal fabrication, plastic injection molding

	Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE		✓ Standard	
			✓ Instruction for use	
			✓ Marking	
	Manufacturer's instructions and information is available	✓	Standar	
§1.4			✓ Instruction for use	
			Markin	
60 -	PPE which may be caught up during use	✓ ·	Standar	
§2.5			✓ Instruction for use	
			Markin	
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety		✓ Standar ✓ Instruction for use	
32.12			✓ Markin	
		√	✓ Standar	
§2.14	Multi-risk PPE		✓ Instruction for use	
			✓ Markin	
	The PPE is intended to protect against mechanical injuries	V	✓ Standar	
§3.3			✓ Instruction for use	
			✓ Markin	
§3.6	Protection against heat and/or fire	✓	✓ Standar	
			✓ Instruction for use	
			✓ Markin	

<u>Available sizes :</u>

Minimum length of glove (mm)	Sizes
220mm	6
230mm	7
240mm	8
250mm	9
260mm	10
270mm	11

Glove constitution:

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		Black	Micro foam Nitrile			0.85-1.5MM
Paim		GREY	Graphene	250g/m2	15	
Back		GREY	Graphene	250g/m2	15	
Cuff		GREY/White	Graphene/Elastic	300g/m2	15	
Binding		White binding	graphene/polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425. This glove is designed mechanical risks, thermal risks. It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity: 5
Size: conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388: 2016

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	A
Impact Protection	-

The levels of performance have been measured on the palm

Thermal hazard EN 407: 2004

Protection offered	Performance levels
Burning behaviour	X
Contact heat	1
Convective heat	X
Radiant heat	X
Small splashes of molten metal	X
Large quantities of molten metal	X

« X »indicates that the glove has not been submitted to the test

TEST REPORTS

Laboratory	CTC	Other
	S180506915_1, H161204900_1, S180100135_2 (DMFu)	
EN 388	H161204897_1, H161204899_1, H161204898_1, H170200371_1, H170200372_1	
EN 407	H170200487_1(Contact heat)	
l ()IDAr	H170200373_1(ANSI-CUT), S170607229_1(ANSI-ABRASION)	

MARKING - PACKAGING

Information printed on the glove:

Logo of Manufacturer:

Logo (€

Glove's reference: 01-101

Article Code: /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram
Address of Manufacturer:

Date of Manufacture (month/year) and/or Serial number:

Marking example:





Method of marking on the glove:

SCREEN PRINT AND SEWN LABEL

Packaging:

EACH PAIR PER POLYBAG, ONE DOZEN PER BIG POLYBAG, 10 DOZEN PER CARTON

PPE subject to ageing:

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity:

MEANS OF CONTROL

We make all inspection based on the acceptance sampling. Materials Conduct inspection on all incoming raw materials and accessory materials. Conduct size checking on all component parts. Conduct visual inspection on defective parts. Checking missing parts before sending to sewers. Inspected for defects, gauged for proper thickness. Quality checking on sewing in areas of appearance, sizing(based on the EN420 sizing standard), weight,labelling, stitches, seaming and component positioning. After coating we will make the sizing, weight,smell,PH,chemic test and cutting ,abrasion test (based on EN388 standard). Finished Products perform random checking(acceptance sampling) before shipment. Quality control is performed under ISO 9001.



INSTRUCTION FOR USE

Glove reference: 01-101

Article code: /

Available sizes: 6 7 8 9 10 11

Glove description:

15 GAUGES Graphene LINER, Micro foam Nitrile palm coating

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018 : innocuousness, comfort, solidity. It has been subject to a UE-type Examination performed by :

C.T.C. (OO75) 4, rue Hermann Frenkel 69367 LYON Cedex 07 FRANCE

Applicable standards:

The glove meets the requirements of the standard EN 420 : 2003 + A1 : 2009 « General requirements for work glove ». Dexterity : 5 Moreover, this glove has been designed for the following applications :

<u>Application</u>: Mechanical hazard - EN 388 : 2016





4 1 2 1 A Levels of performance

<u>Application</u>: Thermal risk - EN 407 2004





X1XXXX
Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	А	(A to F)
Impact Protection		

Burning behaviour	X	(on 4 maxi)
Contact heat	1	(on 4 maxi)
Convective heat	Х	(on 4 maxi)
Radiant heat	Х	(on 4 maxi)
Small splashes of molten metal	Х	(on 4 maxi)
Large quantities of molten metal	Х	(on 4 maxi)

[«] X »indicates that the glove has not been submitted to the test

riginal CTC

Protection limit:

This glove doesn't give a protection for a temperature over 100°C.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity:

Available on : www.qsglove.com